



ZPMV2.E466570
Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

RLX SOLUTIONS INC

23 McCleary Ct, Unit 21
 Concord, ON L4K 3R6 CANADA

E466570

	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam mm(in)	Solder		Max Oper Temp C		Meets UL796 Class DSR	C T I
	Min mm(in)	Edge mm(in)				Thk mic(mil)	Limits C	sec	Flame C		
Mass laminated (multilayered) printed wiring boards, flammability only Recognition.											
RLX-4	0.10 (0.004)	0.31 (0.012)	17 (0.67)	DS	50.8 (2.0)	280	20	130	V-0	All	*
Multilayer printed wiring boards.											
CM	0.08 (0.003)	0.17 (0.007)	17 (0.67) Int:68	DS	50.8 (2.0)	288	10	130	V-0	All	-
RLX-41	0.10 (0.004)	0.20 (0.008)	17 (0.67) Int:34	DS	25.4 (1.0)	280	15	130	V-0	All	*
Multilayer Printed Wiring Boards.											
RLX-H2	0.07 (0.003)	0.21 (0.008)	17 (0.67) Int:68	DS	50.8 (2.0)	288	20	130	V-0	All	*
Multilayer printed wiring boards.											
RLX-M	0.075 (0.003)	0.10 (0.004)	18 (0.71) Int:140	DS	50.8 (2.0)	270	10	130	V-0	All	-
RLX-M1	0.25 (0.010)	0.25 (0.010)	19 (0.75) Int:140	DS	25.4 (1.0)	270	10	130	V-0	All	-
RLX-MF	0.075 (0.003)	0.10 (0.004)	18 (0.71) Int:68	DS	50.8 (2.0)	270	10	105	V-0	All	-
RLX-MR	0.075 (0.003)	0.10 (0.004)	20 (0.79) Int:68	DS	50.8 (2.0)	270	10	105	V-0	All	-
Single layer metal base printed wiring board, flame only recognition.											
RLX-S	-	-	-	SS	-	260	10	-	V-0	-	-
Single Layer Metal Base Printed Wiring Boards.											
RLX-H3	0.17 (0.007)	0.17 (0.007)	17 (0.67)	SS	50.8 (2.0)	288	20	90	V-0	All	*
Single layer printed wiring boards.											
CL	0.08 (0.003)	0.17 (0.007)	17 (0.67)	DS	50.8 (2.0)	288	10	130	V-0	All	-
RLX-11	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	25.4 (1.0)	280	15	130	V-0	All	-
RLX-2	0.10 (0.004)	0.31 (0.012)	17 (0.67)	DS	50.8 (2.0)	280	20	130	V-0	All	3
RLX-21	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	25.4 (1.0)	280	15	130	V-0	All	*
RLX-D	0.075 (0.003)	0.10 (0.004)	18 (0.71)	DS	50.8 (2.0)	270	10	130	V-0	▲	-
Single Layer Printed Wiring Boards.											
RLX-H1	0.07 (0.003)	0.21 (0.008)	17 (0.67)	DS	50.8 (2.0)	288	20	130	V-0	All	*
Single layer printed wiring boards.											
RLX-R	0.075 (0.003)	0.10 (0.004)	20 (0.79)	DS	50.8 (2.0)	270	10	105	V-0	All	-

* - CTI marking is optional and may be marked on the printed wiring board.



Marking: Company name or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2018-02-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".